

Select the Best!

Select...



Pipe Thread Compound with PTFE[△]

SELECT-UNYTE is an all purpose, non-seizing, PTFE thread sealing compound that produces a leak proof seal on all types of metal and plastic threaded connections. **SELECT-UNYTE** is a smooth, grit free, completely homogenized, white PTFE paste. Temperature Range Use: -50°F (-45°C) to 400°F (+204°C).

- **Non-Separating**
- **Grit Free Paste**
- **Adheres to Oily Threads**
- **Easy Cleanup**
- **Safe for PVC & CPVC**
- **Nontoxic/Non Combustible**

FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin*, Zytel*, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon**, Cyclocac***, and all types of metal.

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (210.9 Kg/cm²)

Liquids:

Up to 10,000 PSI (703.0 Kg/cm²)

U.S. FEDERAL SPECIFICATIONS

Select-Unyte exceeds TT-S-1732

AVAILABLE SIZES

Stock#	Size
TF2	2 oz. tube (56 g)
TF4	1/4 pint (118 ml)
TF8	1/2 pint (237 ml)
TF16	1 pint (473 ml)
TF32	1 quart (.95 L)
TF1	1 gal. (3.785 L)
TF5	5 gal. (18.9 L)
TF55	55 gal. (208 L)

*Dupont registered trademark

**Celanese registered trademark

***General Electric Plastics registered trademark

Suitable for use on systems carrying:

Acids, Dilute	Cutting Oils	Helium (Gaseous)	Natural Gas
Air, Compressed	Diesel Exhaust Fluid (DEF)	Hydraulic Oils	Nitrogen (Gaseous)
Aliphatic Solvents	Diesel Fuel Oil	Hydrogen	Petroleum Solvents
Alkalis, Dilute	Fatty Acids	Inert Gases	Propane
Ammonia	Food Processing (JP4, JP5, & JP6)	Jet Fuel	Refrigeration Gases
Brine	Freons (All)	Kerosene	Soap, Liquid
Butane	Gasohol	LP Gases	Steam Lines
Carbon Dioxide	Gasoline [†]	Lacquer	Sugar, Liquid
Castor Oils	Glycol	Mineral Oils	Vegetable Oils
Chlorinated Water	Heating Oils	Naphtha	Water (Potable)
Coal Tar Naphtha			Xyol



Approved for Natural Gas, Propane, LP Gas and Butane.



NSF Standard 14
NSF Standard 61

pw-G/dww/sw



Underwriters Laboratories of Canada
Listed Pipe Joint Compound
Form1 Issue No. 1351

"For a Positive Leak-proof Seal"

Distributed By:



The Industry Standard for Over 100 Years

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358
FAX: 800-537-0588

International

Phone: 330-334-2524
FAX: 330-334-3005

www.joinpipe.com



© 2014 J.C. Whitlam Manufacturing Co.

[△]PolyTetraFluoroEthylene [†]Contact J.C. Whitlam Mfg. Company for compatible blends.