

SELECT-UNYTE

PTFE THREAD SEALING COMPOUND

TF-SPEC

PRODUCT DESCRIPTION

PRODUCT

SELECT-UNYTE Pipe Thread Compound with PTFE[□]

DESCRIPTION

SELECT-UNYTE is an all purpose, non-seizing, PTFE thread sealing compound that produces a leakproof seal on all types of metal and plastic threaded connections. **SELECT-UNYTE** is a smooth, grit free, completely homogenized, white PTFE paste.

- Non-Separating
- Grit Free
- Non-Toxic
- Easy Cleanup
- Adheres to Oily Threads

RECOMMENDED USES

SELECT-UNYTE will not transfer any taste or odor to the system being sealed. Excellent for food and water systems. **SELECT-UNYTE** will never harden, and is an anti-galling compound making it possible to disassemble pipes and bolts easily after years of service. Suitable for PVC and CPVC threaded connections.

Suitable for use on systems carrying:

Acids, Dilute	Hydraulic Oils
Air, Compressed	Hydrogen
Aliphatic Solvents	Inert Gases
Alkalis, Dilute	Jet Fuel(JP4,5&6)
Ammonia	Kerosene
Brine	Lacquer
Butane	L P Gases
Carbon Dioxide	Mineral Oils
Castor Oils	Naphtha
Chlorinated Water	Natural Gas
Coal Tar Naphtha	Nitrogen Gas
Cutting Oils	Petroleum Solvents
Diesel Exhaust	Propane
Fluid (DEF)	Refrigeration
Diesel Fuel Oil	Gases
Fatty Acids	Soap, Liquid
Freons (All)	Steam Lines
Gasohol	Sugar, Liquid
Gasoline [^]	Vegetable Oils
Glycol	Water (Potable)
Heating Oils	Xylol
Helium, Gaseous	

COLOR/CONSISTENCY

White brushable paste of smooth, grit free consistency. **SELECT-UNYTE** has an indefinite shelf life.

TEMPERATURE RANGE USE

Gases:

-50°F (-46°C) to 400°F (204°C)

Liquids:

-50°F (-46°C) to 400°F (204°C)

Brushable to:

-50°F (-46°C)

PRESSURE RANGE USE

Gases:

up to 3,000 PSI (211 kg/cm²)

Liquids:

up to 10,000 PSI (703 kg/cm²)

DRYING TIME*

The system may be pressurized immediately after assembly. Soft set, non-hardening.

FOR USE ON THREADED

ABS, PVC, CPVC, Delrin*, Zytel*, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon**, Cyclocac***, and all types of metal.

CORROSIVENESS

SELECT-UNYTE is non-corrosive, and prevents the corrosion and seizing of threads.

U.S. FEDERAL SPECIFICATIONS

SELECT-UNYTE exceeds TT-S-1732.

ENVIRONMENTAL STATEMENT

SELECT-UNYTE is formulated with non-toxic inert oils and is free from any lead containing ingredients.

WEIGHT PER U.S. GALLON

11.9 lbs. (5.4 kg) ± 0.2

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Squeeze Tube	
TF2	2 oz. (.056 kg)
Brush Top Can	
TF4	¼ pint (118 ml)
TF8	½ pint (237 ml)
TF8A (display box)	½ pint (237 ml)
TF16	1 pint (473 ml)
TF32	1 quart (.95 L)
1 Gallon Metal Can w/ Handle	
TF1	1 gal. (3.785 L)
5 Gallon Plastic Pail w/ Handle	
TF5	5 gal. (18.9 L)
55 Gallon Open Head Steel Drum	
TF55	55 gal. (208 L)

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
TF2	11 lbs. (5.0 kg)	72
TF4	15 lbs. (6.8 kg)	24
TF8	23 lbs. (10.4 kg)	24
TF8A	13 lbs. (5.9 kg)	12
TF16	22 lbs. (10.0 kg)	12
TF32	43 lbs. (19.5 kg)	12
TF1	52 lbs. (23.6 kg)	4
TF5	66 lbs. (29.9 kg)	1
TF55	640 lbs. (290.3 kg)	1

DIRECTIONS FOR USE

1. Stir well before using.
2. Brush liberally onto male threads.
3. Make up joint in a normal manner.

On large diameter pipe 2" (5.08 cm) and up, first wrap the pipe threads with two or more thicknesses of **Tape-Unyte®** PTFE Tape, and then apply **SELECT-UNYTE** over the tape.



Underwriters' Laboratories of Canada Listed for Natural Gas, Gasoline, Petroleum Oils, Propane & Butane



pw-G/dww/sw
Meets NSF Standard 14 NSF Standard 61



Approved for Natural Gas, Propane, LP Gas and Butane

TF-SPEC

© 2017 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

[□]PolyTetraFluoroEthylene ^{*}Contact J.C. Whitlam Mfg. Co. for compatible blends.

^{*}Dupont registered trademarks. ^{**}Celanese registered trademark. ^{***}General Electric Plastics registered trademark.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information. ^{*}Note: Both set time and cure time are affected by humidity and temperature and may vary greatly ±.



P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com