

TALON™ PTFE TAPE



FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin*, Zytel*, FlowGuard Gold** CPVC, Blazemaster** CPVC, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon***, Cyclocac****, and all types of metal.

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (210.9 Kg/cm²)

Liquids:

Up to 10,000 PSI (703.0 Kg/cm²)

TENSILE STRENGTH

LOGITUDINAL

15N / mm²

ELONGATION

>100%

THICKNESS

.0035" ± 10%

SPECIFIC GRAVITY

0.8 g/cm³

U.S. FEDERAL

SPECIFICATIONS

TALON TAPE

Meets MIL-T-27730A

AVAILABLE SIZES

Stock#	Size
TL1429	1/2" x 1429"
TLW1429	3/4" x 1429"
TLX1429	1" x 1429"

*Dupont registered trademark

** FlowGuard GOLD and Blazemaster are registered trademarks of The Lubrizol Corporation.

***Celanese registered trademark

****General Electric Plastics registered trademark

J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005

www.TalonPTFE.com



© 2018 J.C. Whitlam Manufacturing Co.

TALON™ Professional Grade PTFE Tape

TALON™ PTFE TAPE is a Heavy Mil and High Density Tape that offers *Freedom from Leaks™* virtually on all types of threaded connections.

Each size comes in a 1429 inch roll (36.3 m). TALON™ PTFE TAPE is suitable for any threaded pipe carrying dilute acids, compressed air, aliphatic solvents, dilute caustics, cutting oils, diesel fuel oil, hydraulic fluids, L.P. Gas, natural gas, petroleum solvents, steam, vegetable oils, water and many more.

Seals threads on many threaded connections including:

- **Stainless Steel**
- **Cast Iron**
- **PVC, CPVC, and ABS Fittings**
- **Brass and Chrome**
- **Gas Systems**
- **And More !**



1429 Inch (36.3 m) Long Roll.

**50% More Tape
than the Leading Brand!**

Distributed By:



W WHITLAM

The Industry Standard for Over 100 Years

PTFE = PolyTetraFluoroEthylene